

Baureihe BWP 22

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW	Drehzahl min ⁻¹	Freier Durchgang mm	Druckstutzen mm	Saugstutzen mm	Aufstellvarianten
BWP 22-20	31	15.5	0.75 - 7.5	750 - 1.450	65	80	80	HS, VS
BWP 22-21	31	26.5	4.0 - 7.5	2.900	65	80	80	HS, VS
BWP 22-30	46	17.5	1.5 - 7.5	960 - 1.450	80	100	100	HS, VS
BWP 22-40	43	15.5	1.5 - 7.5	960 - 1.450	100	100	100	HS, VS
BWP 22-41	49	18	1.5 - 7.5	960 - 1.450	100	100	125	HS, VS

Baureihe BWP 42

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW	Drehzahl min ⁻¹	Freier Durchgang mm	Druckstutzen mm	Saugstutzen mm	Aufstellvarianten
BWP 42-20	31	54	5.5 - 15.0	1.450 - 2.900	65	80	80	H, HS, HM, HF, V, VS, VM, KM
BWP 42-21	34	37.5	5.5 - 15.0	2.900	65	80	80	H, HS, HM, HF, V, VS, VM, KM
BWP 42-30	48	18	3.0 - 15.0	1.450 - 2.900	80	100	100	H, HS, HM, HF, V, VS, VM, KM
BWP 42-33	35	43	7.5 - 15.0	2.900	80	100	100	H, HS, HM, HF, V, VS, VM, KM
BWP 42-40	43	15.5	3.0 - 15.0	960 - 1.450	100	100	100	H, HS, HM, HF, V, VS, VM, KM
BWP 42-41	64	22	3.0 - 15.0	960 - 1.450	100	100	125	H, HS, HM, HF, V, VS, VM, KM

Baureihe BWP 60

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW	Drehzahl min ⁻¹	Freier Durchgang mm	Druckstutzen mm	Saugstutzen mm	Aufstellvarianten
BWP 60-30	58	79	4.0 - 55.0	960 - 2.900	80	100	100	H, HM, HF, V, VM, KM
BWP 60-50	118	21	11.0 - 45.0	960 - 1.450	125	150	150	H, HM, HF, V, VM, KM
BWP 60-60	134	30	11.0 - 45.0	960 - 1.450	150	200	200	H, HM, HF, V, VM, KM

Baureihe BWP 62

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW	Drehzahl min ⁻¹	Freier Durchgang mm	Druckstutzen mm	Saugstutzen mm	Aufstellvarianten
BWP 62-11	20	112	15.0 - 55.0	2.900	50	50	65	H, HM, HF, V, VM, KM
BWP 62-32	53	74	11.0 - 55.0	2.900	80	100	100	H, HM, HF, V, VM, KM
BWP 62-41	75	49	11.0 - 45.0	960 - 1.450	100	100	125	H, HM, HF, V, VM, KM