

Baureihe DWP 22-10/12 Duplex - 50 mm freier Durchgang

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW (p2)	Drehzahl min ⁻¹	Nennstrom A	Spannung	Startart	Druckstutzen mm	Saugstutzen mm
DWP 22-10 DC-U	10	5.7	1.5	1.420	3.6	3ph 400V 50Hz	direkt	50	50
DWP 22-10 BB-U	12	12.5	1.5	2.790	3.3	3ph 400V 50Hz	direkt	50	50
DWP 22-10 BD-U	13	15.5	2.2	2.830	4.5	3ph 400V 50Hz	direkt	50	50
DWP 22-10 BE-U	13.5	18.5	2.6	2.800	5.6	3ph 400V 50Hz	direkt	50	50
DWP 22-10 BH-U	14	25	4.0	2.840	8.5	3ph 400V 50Hz	direkt	50	50
DWP 22-12 DC-U	17	8	1.5	1.420	3.6	3ph 400V 50Hz	direkt	65	65
DWP 22-12 DD-U	20	9	2.2	1.375	5.0	3ph 400V 50Hz	direkt	65	65

Baureihe DWP 22-20/22 Duplex - 65 mm freier Durchgang

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW (p2)	Drehzahl min ⁻¹	Nennstrom A	Spannung	Startart	Druckstutzen mm	Saugstutzen mm
DWP 22-20 BB-U	12.5	13	1.5	2.790	3.3	3ph 400V 50Hz	direkt	65	65
DWP 22-20 BD-U	17	13	2.2	2.830	4.5	3ph 400V 50Hz	direkt	65	65
DWP 22-20 BE-U	16.5	16	2.6	2.800	5.6	3ph 400V 50Hz	direkt	65	65
DWP 22-20 BH-U	20	21	4.0	2.840	8.5	3ph 400V 50Hz	direkt	65	65
DWP 22-22 DC-U	21.5	10	1.5	1.420	3.6	3ph 400V 50Hz	direkt	67	72
DWP 22-22 DD-U	24	12.5	2.2	1.375	5.0	3ph 400V 50Hz	direkt	67	72
DWP 22-22 DG-U	23.5	17	3.5	1.385	7.7	3ph 400V 50Hz	direkt	67	72

Baureihe DWP 22-41 Duplex - 100 mm freier Durchgang

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW (p2)	Drehzahl min⁻¹	Nennstrom A	Spannung	Startart	Druckstutzen mm	Saugstutzen mm
DWP 22-41 DC-U	34	6	1.5	1.420	3.6	3ph 400V 50Hz	direkt	100	110
DWP 22-41 DD-U	32	7.7	2.2	1.375	5.0	3ph 400V 50Hz	direkt	100	110
DWP 22-41 DG-U	36	11	3.5	1.385	7.7	3ph 400V 50Hz	direkt	100	110