

Baureihe DWP 42-20/21 Duplex - 65 mm freier Durchgang

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW (p2)	Drehzahl min ⁻¹	Nennstrom A	Spannung	Startart	Druckstutzen mm	Saugstutzen mm
DWP 42-20 BJ-U	13.5	30	5.0	2.790	9.8	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-20 BR-U	26	46	9.0	2.900	17.2	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-20 BZ-U	27	54	13.0	2.915	24.2	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-20 DJ-U	27	16	5.0	1.420	11.2	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-21 BJ-U	24	23	5.0	2.790	9.8	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-21 BR-U	27	31	9.0	2.900	17.2	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-21 BZ-U	26	37	13.0	2.915	24.2	3ph 400V 50Hz	Stern-Dreieck	67	72

Baureihe DWP 42-41 Duplex - 100 mm freier Durchgang

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW (p2)	Drehzahl min ⁻¹	Nennstrom A	Spannung	Startart	Druckstutzen mm	Saugstutzen mm
DWP 42-41 DJ-U	51	14.5	5.0	1.420	11.2	3ph 400V 50Hz	Stern-Dreieck	100	110
DWP 42-41 DL-U	54	16	6.0	1.395	13.1	3ph 400V 50Hz	Stern-Dreieck	100	110
DWP 42-41 DO-U	57	19	7.5	1.390	15.2	3ph 400V 50Hz	Stern-Dreieck	100	110
DWP 42-41 DU-U	60	22	10.5	1.420	21.2	3ph 400V 50Hz	Stern-Dreieck	100	110
DWP 42-41 DZ-U	66	22	13.0	1.420	26.1	3ph 400V 50Hz	Stern-Dreieck	100	110

Baureihe DWP 62-41 Duplex - 100 mm freier Durchgang

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW (p2)	Drehzahl min ⁻¹	Nennstrom A	Spannung	Startart	Druckstutzen mm	Saugstutzen mm
DWP 62-41 LI-U	75	42	34.0	1.440	66.4	3ph 400V 50Hz	Stern-Dreieck	100	120