

Baureihe DWP 42-20/21 - 65 mm freier Durchgang

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW (p2)	Drehzahl min ⁻¹	Nennstrom A	Spannung	Startart	Druckstutzen mm	Saugstutzen mm
DWP 42-20 BJ	13.5	30	5.0	2.790	9.8	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-20 BR	26	46	9.0	2.900	17.2	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-20 BZ	27	54	13.0	2.915	24.2	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-20 DJ	27	16	5.0	1.420	11.2	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-21 BJ	24	23	5.0	2.790	9.8	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-21 BR	27	31	9.0	2.900	17.2	3ph 400V 50Hz	Stern-Dreieck	67	72
DWP 42-21 BZ	26	37	13.0	2.915	24.2	3ph 400V 50Hz	Stern-Dreieck	67	72

Baureihe DWP 42-30/32/33 - 80 mm freier Durchgang

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW (p2)	Drehzahl min ⁻¹	Nennstrom A	Spannung	Startart	Druckstutzen mm	Saugstutzen mm
DWP 42-30 DJ	43	13	5.0	1.420	11.2	3ph 400V 50Hz	Stern-Dreieck	100	100
DWP 42-30 DL	50	17	6.0	1.395	13.1	3ph 400V 50Hz	Stern-Dreieck	100	100
DWP 42-30 DO	50	16.5	7.5	1.390	15.2	3ph 400V 50Hz	Stern-Dreieck	100	100
DWP 42-32 BJ	30	20.5	5.0	2.790	9.8	3ph 400V 50Hz	Stern-Dreieck	100	80
DWP 42-32 BR	35	33	9.0	2.900	17.2	3ph 400V 50Hz	Stern-Dreieck	100	80
DWP 42-32 BZ	34	35	13.0	2.915	24.2	3ph 400V 50Hz	Stern-Dreieck	100	80
DWP 42-33 BZ	34	44.5	13.0	2.915	24.2	3ph 400V 50Hz	Stern-Dreieck	100	80

Baureihe DWP 42-40/41/43 - 100 mm freier Durchgang

Pumpentyp	Max. Fördermenge l/s	Max. Förderhöhe m	Motor kW (p2)	Drehzahl min⁻¹	Nennstrom A	Spannung	Startart	Druckstutzen mm	Saugstutzen mm
DWP 42-40 DJ	45	13.5	5.0	1.420	11.2	3ph 400V 50Hz	Stern-Dreieck	100	100
DWP 42-40 DL	48	15	6.0	1.395	13.1	3ph 400V 50Hz	Stern-Dreieck	100	100
DWP 42-41 DO	57	19	7.5	1.390	15.2	3ph 400V 50Hz	Stern-Dreieck	100	110
DWP 42-41 DU	60	22	10.5	1.420	21.2	3ph 400V 50Hz	Stern-Dreieck	100	110
DWP 42-41 DZ	66	22	13.0	1.420	26.1	3ph 400V 50Hz	Stern-Dreieck	100	110
DWP 42-43 FE	34	8.5	2.4	905	5.7	3ph 400V 50Hz	Stern-Dreieck	100	100